In the claims:

Claims 1-3 (delete)

Claim 4 (currently amend) An A apparatus for securing an object appliance to a support surface comprising:

a first base having a substantially planar section and opposingly located stepped ends;

a second base having a substantially planar section and opposingly located lipped ends each of which form forms a channel:

at least one moveable tab depending from said second base;

said first and second bases sized to allow said first base to be nestable within said second base and movable between first and second positions with respect to said second base;

said first base positionable between a first and second position with respect to said second base;

one of said stepped ends sized to be insertable into one of said channels formed by one of said lipped ends so as to permit said first based to be placed into a said first position;

in said first position, the other stepped end of said first base is positioned to allow engaging said moveable tab to be engaged by said stepped end;

said first base slideable with respect to said second base to permit said first base to be positioned into a said second position with respect to said second base;

in said second position, said moveable tab is positioned against to abut a portion of said stepped portion of said second first base to interlock said bases [.]; and

a rod sized to fit into an opening whereby said rod may engage said at least one moveable tab so as to unlock said bases.

Claim 5 (original) The apparatus of claim 4 wherein said lipped ends of said second base act as stops which prevent said first base from being removed from said second base when said first base is in said second position.

Claim 6 (original) The apparatus of claim 4 wherein said at least one moveable tab is located in a protected chamber formed when said bases are interlocked.

Claims 7-8 (delete)